

CCU09A402RNIUX

indoor

> CONTACT US



The CCU series roof-mounted cooling units represent an ideal solution for cooling battery electrical panels or when accessibility and lateral space are limited, ensuring high technical and safety standards. In all models, the polyurethane gasket is laid by machine, significantly reducing installation times.

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Cooling Capacity L35L35	975/1075 3327/3668	W BTU/hr
Cooling Capacity L35L50	795/815 2713/2781	W BTU/hr
ELECTRICAL DATA		
Rated Voltage	380/400/440/460/480	V a.c. 2 ~ at 50/60 Hz
Rated Current	2.1/2.4	A at 480 V a.c. 2 ~
Rated Current	2.2/2.5	A at 460 V a.c. 2 ~
Rated Current	2.3/2.6	A at 440 V a.c. 2 ~
Rated Current	2.5/2.8	A at 400 V a.c. 2 ~
Rated Current	2.7/3	A at 380 V a.c. 2 ~
Rated Power L35L35	445/525	W
Rated Power L35L50	495/595	W
Frequency	50/60	Hz
Max Current	13	A

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

CCU09A402RNIUX

indoor

> CONTACT US

Technical data		
Fuse T	6	A
GENERIC DATA		
Casing Material	Painted Steel	
RAL Number	7035	
Electrical Connection	Connector	
Refrigerant Number	R134a	
Refrigerant Charge	210	g
Maximum Allowable Pressure	HP 2.4/LP 0.6	MPa
ENVIRONMENTAL AND THERMAL DATA		
Protection Degree Internal Circuit	IP54	
Operating Temperature	20÷50	°C
	68÷122	°F


Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

CCU09A402RNIUX

indoor

> CONTACT US

Technical drawing mm (in)



Cooling Capacity vs Temperature




Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.




Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.